

Air Mover Range

A range of high performance carpet and room dryers, that significantly reduce drying time of carpets, walls and ceilings, and are ideal for use after floods, spillages or extraction cleaning

Air Movers

- High airflow for rapid drying
- Aids air circulation and ventilation
- Three-speed switch to select the optimal airflow for the job
- High density Polyethylene housing for durability
- Reinforced motor mounting for reliability and long life
- Easy-carry handles for comfortable portability
- Model available with built-in trolley for easy transport

Whole Room Dryer

- 360° directed air flow allows rooms to be dried without repositioning dryer
- Heavy-duty castors position unit at optimum downdraft™ height
- One dryer can dry a typical office or room in as little as 15 minutes
- High density polyethylene housing for durability

Axial Fan

- High-volume, high-velocity airflow for the fastest possible drying
- One of the most effective solutions for structural drying after floods or leaks
- Model available with built in trolley for easy transport



A Tacony Company



Air Mover

Optional carpet clamp enables air to be directed under the carpet speeding up the drying of both the carpet and underlying floor



Air Mover

Built in kickstand that raises airflow off the floor for rapid drying of floor polishes, seals, paint or other coatings



Whole Room Dryer

Downdraft drying pulls warmer air from above driving it down and out across the entire surface of the carpet



Whole Room Dryer

Built-in trolley with telescopic handle for convenient transport



Axial Fan

Optional castor kit for easy transport and to provide downdraft drying



All three machines offer multiple position versatility and are stackable for easy transport and storage

Technical Specification

Model		Air Mover	Air Mover with trolley	Whole Room Dryer	Axial Fan	Axial Fan with trolley
Product Code		AM	AM/T	WRD	AF	AF/T
Voltage AC (~)/ Frequency	V/ Hz	230/ 50-60	230/ 50-60	230/ 50-60	230/ 50-60	230/ 50-60
Motor power	W	713	713	414	414	414
Airflow rate	m³/h	2620	2620	5950	5100	5100
	cfm	1540	1540	3500	3000	3000
Speeds		3	3	2	2	2
Thermal overload		✓	✓	✓	✓	✓
Kickstand		✓	✓			
Telescopic handle and wheels			✓	✓		✓
Dimensions (L x W x H)	cm	47 x 44 x 54	59 x 44 x 54	59 x 68 x 59	59 x 57 x 56	59 x 68 x 56
Weight	kg	15	17	24	17	18
Cable length	m	6	6	6	6	6
Warranty		1 year				

Call us for a free demonstration today!

Sales Hotline: +44 (0) 23 8070 6600

Truvox International Limited, Third Avenue, Millbrook, Southampton, Hampshire England SO15 0LE

Tel: +44 (0) 23 8070 2200 Fax: +44 (0) 23 8070 5001 Email: truvox@truvox.com Web: www.truvox.com

Truvox International is a BSI Registered Company and our policy is one of continuous development. We reserve the right to change specifications without prior notification.

TRU-AMUK-0411

